

# Donga Door

Inswing



Motisan donga doors are designed and engineered in Australia to meet Australian standards and requirements. These pre-hung steel doors feature a dual frame system, allowing for easy installation in various applications, including transportable buildings, container modifications, steel frame sheds, and block walls.

With Galvanized door leaf and frame, UV-resistant powder coating, a durable four-sided door frame with gasket, and fire-resistant rockwool insulation, these doors are built to withstand extreme weather conditions, including cyclone zones. These doors also feature a custom-made bottom frame with three slot holes for effective water drainage, ensuring a tight weather seal.

# SPECIFICATIONS

<b>Structural Material</b>	Galvanised steel	
<b>Steel thickness</b>	Door leaf 0.8mm / Door frame 1.5mm	
<b>Finish</b>	UV-Resistant Powder coating	
<b>Infill Insulation</b>	Fire-resistant Rockwool(Mineral Wool) R-value 1.40 m <sup>2</sup> K/w	
<b>Hinge</b>	3 Stainless Steel Hinges	
<b>Size(mm)</b>	Door leaf	Clear opening
	820×2075×50	794×2050
	920×2075×50	894×2050
	1020×2075×50	994×2050
	customize for other size requirement	
<b>Swing direction</b>	Inswing	
<b>Options</b>	<ul style="list-style-type: none"> <li>• Double-glazing view windows</li> <li>• Stainless steel kick plates</li> <li>• Powder Coating in Various Colors or Dual-Color</li> </ul>	

# LOCKS

<b>Lever</b>	<b>DDA Compliant</b>	<b>Mortice</b>	<b>Security Lock</b>
			